

TYPICAL GAUGES COMBINATIONS (TOP/BODY/BOTTOM)			UN MARK STANDARD WORLWIDE	UN MARK SPECIAL WORLDWIDE
SSCI	SEFA	JSDA		
1.4/1.4/1.4	1.5/1.5/1.5 1.5/1.2/1.5		X 1.2/250 X 1.2/250 X 1.2/250	X 2.0/400 X 2.0/400 X 2.0/400
1.1/1,1/1.1	1.2/1.2/1.2 1.2/1.1/1.2 1.2/1.0/1.2	1.2/1.2/1.2 1.2/1.0/1.2	X 1.2/250 X 1.2/250 X 1.2/250 X 1.2/250	X 1.8/300 X 1.8/300 X 1.8/300 X 1.8/300
1.0/1.0/1.0 1.2/0.9/1.2 1.1/0.8/1.1	1.0/1.0/1.0 1.0/0.9/1.0 1.0/0.8/1.0	1.0/1.0/1.0	X 1.2/250 X 1.2/250 X 1.2/250 X 1.2/250 X 1.2/250	
0.8/0.8/0.8	0.8/0.8/0.8 0.8/0.7/0.8		Y 1.4/150 Y 1.4/150	

In bold : most frequently used gauges combinations .

Special marks :Only for the very few products requiring a UN marking higher than X1.2/250

: worldwide